

# **FL40 Flat Wall Panel**

#### **PRODUCT PARAMETERS**

Panel Thickness:		
2"	2.5"	3"
Insulating Values (R):**		
16	20	24

Panel Width: 40" (36" available)

Panel Length: 8' minimum to 32' maximum

**Insulation Material:** CFC-free, foamed-in-place polyisocyanurate foam (2.1 to 2.5 PCF density)

Joint Configuration: Offset tongue-and-groove with concealed fastener

**Metal Facings:** 22-gauge (exterior) and 26-gauge (interior)

Coatings: PVDF & SMP (other coatings available)

Accessories: Fasteners, clips, sealants and brakeformed flashings

Available in 1-hour fire-rated panel: FL40-F (4.5" R-32)

### **TESTED & APPROVED**

The insulated panel products have been extensively tested under a variety of North American standards:

FM 4880: Class 1 Fire Rating FM 4881: Class 1 Exterior Wall System CAN/ULC S101: Fire Endurance CAN/ULC S134: Fire Test of Exterior Wall Assemblies ASTM C518/C1363: Thermal Transmission ASTM E283: Air Infiltration ASTM E331: Water Penetration ASTM E72: Structural Strength ASTM E84: Flame Spread AAMA 501.1: Air/Water Infiltration

Miami-Dade County Product Control Approved Florida Approved



\*\*R-Value tested in accordance with ASTM C518/C1363 at 40°F mean temperature, adjusted for a windspeed of 15 mph.

## INNOVATIVE. ADAPTABLE. ENERGY EFFICIENT.

FL40 flat wall panels are produced with a standard embossed face and offer a perfect solution for designers seeking a high-end architectural look with all the thermal benefits that insulated metal panels offer.

### FEATURES AND BENEFITS

- Can be installed either vertically or horizontally. The horizontal assembly incorporates a clean, simple end joint design that utilizes a unique self-aligning prepainted aluminum extrusion.
- The panel's overlapping joint is self-aligning and allows for easy sealant application at the panel joinery.
- The standard exterior metal surface is 22-gauge embossed G-90 galvanized steel with standard PVDF and SMP exterior coatings (other coatings may be available).
- The standard interior metal surface is embossed 26-gauge Imperial White.
- The panel arrives on-site in one piece and requires a simple one-step installation, reducing construction time and costs.

Vulcan Steel Structures, Inc. 500 Vulcan Parkway Adel, GA 31620 1-800-258-3369 www.vulcansteel.com sales@vulcansteel.com

These contents are for general information only and are not intended to serve as any type of advice. Every effort is made to ensure the accuracy of the information included herein and it is believed to be accurate and reliable as of the date of publication. Vulcan Steel Structures does not warrant or represent the accuracy or reliability of any information included in this brochure. Any reliance on any information without consultation with Vulcan Steel Structures or a duly authorized representative shall be at the user's own risk.