

# **SR2 Standing Seam Roof Panel**

#### PRODUCT PARAMETERS

Panel Thickness:			
3.25"	4"	5"	6"
Insulating Values (R):**			
26	32	41	49

Panel Width: 40"

**Panel Length:** 8' minimum to 40' maximum based on a 48' flatbed trailer length (consult your sales representative for other available lengths)

**Insulation Material:** CFC-free, foamed-in-place polyisocyanurate foam (2.1 to 2.5 PCF density)

Joint Configuration: 90° field seamed

Metal Facings: 26-gauge galvanized steel (22

gauge, 24 gauge available)

**Coatings:** PVDF and SMP (other coatings available) **Accessories:** Fasteners, clips, sealants and brake-

formed flashings

### **TESTED & APPROVED**

The insulated panel products have been extensively tested under a variety of North American standards:

FM 4880: Class 1 Fire Rating
FM 4471: Class 1 Roof Assembly
CAN/ULC S102: Flame Spread
CAN/ULC S126: Flame Spread (Roof)
ASTM C518/C1363: Thermal Transmission

ASTM E1646: Water Penetration ASTM E1680: Air Infiltration ASTM E72: Structural Strength

Florida Approved



\*\*R-Value tested in accordance with ASTM C518/C1363 at 40°F mean temperature, adjusted for a windspeed of 15 mph.

# INNOVATIVE, ADAPTABLE, ENERGY EFFICIENT,

SR2 standing seam roof panel has the look of traditional standing seam integrated with the benefits of an insulated metal panel—a great alternative to field-assembled roofing components.

## **FEATURES AND BENEFITS**

- Field-seamed, hidden fastener joinery provides maximum protection against the elements.
- The trapezoidal rib design provides added strength against potential foot traffic damage compared to other standing seam roof products.
- The standard exterior metal surface is smooth 26-gauge G-90 galvanized steel with standard PVDF and SMP exterior coatings (other coatings may be available).
- The standard interior metal surface is embossed 26-gauge Imperial White.
- The panel arrives on-site in one piece and requires a simple one-step installation, reducing construction time and costs.



500 Vulcan Parkway Adel, GA 31620 1-800-258-3369 www.vulcansteel.com sales@vulcansteel.com